

Natural Teak Oil

Page 1 of 2
Resource Code 119905
June 2011

DESCRIPTION

- Wattyl Natural (Scandinavian) Teak Oil is a two part system which utilises Wattyl ESTAPOL® Interior Polyurethane Matt (D5.19) and Natural Teak Oil to produce an attractive natural oil finish on teak or similar timbers. It is designed to impart a very smooth feel to the finish.

PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- Imparts a dry but very smooth feel to the sealed timber surface.
- Duplicates the finish applied to Danish style furniture and interior décor.

COLOURS AND GLOSS

- Clear
- Matt

BASIC DATA

- Surface Dry** Twelve (12) hours
- Recoat** N/A
All figures are quoted 25 °C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- Coverage per coat** up to 20 M²/L (depending on the texture, surface porosity and method of application).
- Wet Film Thickness** 2 microns
- Dry Film Thickness** 0.5 micron
- Thinning** Not required
- Clean up** Thoroughly clean equipment with mineral turps.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on interior domestic furniture, plywood panelling, lining boards, office furniture, staircase handrails, shop fittings etc.
- Ideal for rejuvenating previously sealed furniture.
- Not** suitable on surfaces treated with a wax finish.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- New Timber**
Ensure all new timber is free of dirt or grease and dry. Fill nail holes or cracks with Wattyl Timber Putty (D1.08) in a matching colour. Allow to dry. Sand smooth and remove dust.

INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Stain if required with Wattyl Traditional Stain (D5.02) or Wattyl Colourwood Interior Stain (D5.01). Allow to dry.
- Apply two (2) coats Wattyl ESTAPOL® Matt (D5.19) at twelve (12) hours intervals then allow 48 hours to dry. Lightly sand along the grain with fine sandpaper and remove dust.
Wet the surface with Wattyl Natural Teak Oil and while wet, rug vigorously along the grain with a non soaped household steel wool pad until uniformly smooth. Remove surplus oil with a soft, clean cloth.
- Rejuvenating Oil Finished and previously sealed Furniture**
Apply Wattyl Natural Teak Oil with a soft cloth and while wet rub vigorously along the grain. Wipe clean with a soft clean cloth.

SAFETY DATA

- **Caution** Flammable
Provide adequate ventilation during use.
Soak all used cloths in water immediately after use as they may self ignite.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 250, 500 ml, 1 and 4 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.